



DECLARATION OF PERFORMANCES

01.0008/2019

Annex III CPR - Regulation EU n. 305/2011 - Implementing Regulation EU n. 159/2014

Unique identification code of the product-type: **COLL BLOCK**

Intended use: Factory made designed general purpose masonry mortar (G) for use in elements subject to structural requirements

Manufacturer: Vimark S.r.l. - Strada Spartafino, 2 - 12016 Peveragno (CN) - Italia

Authorised representative: -

System/s of AVCP: System no. 2+
System no. 4 for reaction to fire

Harmonised standard: EN 998-2:2016

Notified bodies: no. 1372 Tecno Piemonte S.p.A.

Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Compressive strength	Category M10	5.4.1 EN 998-2
Bond strength	0.15 N/mm ²	5.4.2 EN 998-2
Contents of chlorides	< 0.01 % Cl	5.2.2 EN 998-2
Reaction to fire	Class A1	5.6 EN 998-2
Water absorption	< 0.2 kg (m ² x min ^{0.5})	5.4.3 EN 998-2
Water vapour permeability	μ 5/20	5.4.4 EN 998-2
Thermal conductivity	0.61 W/mK (tab. Mean value; P=50%)	5.4.6 EN 998-2
Durability	Evaluation based on provisions valid in the intended place of use of the mortar	5.4.7 EN 998-2
Dangerous substances	See MSDS	Note ZA.1 998-2

Appropriate Technical Documentation and/or Specific Technical Documentation: see technical data sheet
see MSDS

Website where the copy of the declaration of performance is made available: www.vimark.com/en/

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

02.04.2019

VIMARK S.r.l. Peveragno (CN) Italy

Marco Dutto



Vimark S.r.l.
Strada Spartafino, 2 - 12016 Peveragno (CN) Italy
13
01.0008/2019

EN 998-2:2016

COLL BLOCK

Factory made designed general purpose masonry mortar (G) for use in elements subject to structural requirements

Compressive strength	Category M10
Bond strength	0.15 N/mm ²
Contents of chlorides	< 0.01 % Cl
Reaction to fire	Class A1
Water absorption	< 0.2 kg (m ² x min ^{0.5})
Water vapour permeability	μ 5/20
Thermal conductivity	0.61 W/mK (tab. Mean value; P=50%)
Durability	Evaluation based on provisions valid in the intended place of use of the mortar
Dangerous substances	See MSDS