



DECLARATION OF PERFORMANCES

08.0012/2018

Annex III CPR - Regulation EU n. 305/2011 - Implementing Regulation EU n. 159/2014

Unique identification code of the product-type: **MASTERFIX**

Intended use: Normal setting cementitious adhesive with reduced slip and extended open time for internal and external tiling (C1TE)

Manufacturer: Vimark S.r.l. - Strada Spartafino, 2 - 12016 Peveragno (CN) - Italia

Authorised representative: -

System/s of AVCP: System no. 3
System no. 4 for reaction to fire

Harmonised standard: EN 12004-1:2017

Notified bodies: -

Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	F Class	EN 12001-2
Early tensile adhesion strength	NPD	EN 12001-2
Initial tensile adhesion strength	$\geq 1,0 \text{ N/mm}^2$	EN 12001-2
Tensile adhesion strength after heat ageing	$\geq 0,5 \text{ N/mm}^2$	EN 12001-2
Tensile adhesion strength after water immersion	$\geq 0,5 \text{ N/mm}^2$	EN 12001-2
Tensile adhesion strength after freeze-thaw cycles	$\geq 0,5 \text{ N/mm}^2$	EN 12001-2
Release of dangerous substances	See MSDS	EN 12001-1


Appropriate Technical Documentation and/or Specific Technical Documentation: see technical data sheet
see MSDS

Website where the copy of the declaration of performance is made available: www.vimark.com/en/

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

03.05.2018
VIMARK S.r.l. Peveragno (CN) Italy


Marco Dutto



Vimark S.r.l.
Strada Spartafino, 2 - 12016 Peveragno (CN) Italy
09
08.0012/2018

EN 12004-1:2017

MASTERFIX

Normal setting cementitious adhesive with reduced slip and extended open time for internal and external tiling (C1TE)

Reaction to fire	F Class
Early tensile adhesion strength	NPD
Initial tensile adhesion strength	$\geq 1,0 \text{ N/mm}^2$
Tensile adhesion strength after heat ageing	$\geq 0,5 \text{ N/mm}^2$
Tensile adhesion strength after water immersion	$\geq 0,5 \text{ N/mm}^2$
Tensile adhesion strength after freeze-thaw cycles	$\geq 0,5 \text{ N/mm}^2$
Release of dangerous substances	See MSDS