



DECLARATION OF PERFORMANCES

08.0015/2021

Annex III CPR - Regulation EU n. 305/2011 - Implementing Regulation EU n. 159/2014

Unique identification code of the product-type: FLEXP TWO

Intended use:

Water based waterproofing product, liquid applied, cement modified with polymer, with improved crack-bridging capacity at very low temperature (-20°C) and resistant to contact with chlorinated water (CMO2P), intended for external installation on walls and floors and pools below ceramic tiles (bonded with an C2 according to EN 12004)

Manufacturer:

Vimark S.r.l. - Strada Spartafino, 2 - 12016 Peveragno (CN) - Italia

Authorised representative:

-

System/s of AVCP:

System no. 3
System no. 4 for reaction to fire

Harmonised standard:

EN 14891:2012

Notified bodies:

-

Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Initial tensile adhesion strength	≥ 0,5 N/mm ²	A.6.2 EN 14891
Tensile adhesion strength after water contact	≥ 0,5 N/mm ²	A.6.3 EN 14891
Tensile adhesion strength after heat ageing	≥ 0,5 N/mm ²	A.6.5 EN 14891
Tensile adhesion strength after freeze-thaw cycles	≥ 0,5 N/mm ²	A.6.6 EN 14891
Tensile adhesion strength after contact with lime water	≥ 0,5 N/mm ²	A.6.9 EN 14891
Tensile adhesion strength after contact with chlorinated water	≥ 0,5 N/mm ²	A.6.7 EN 14891
Waterproofing	no penetration	A.7 EN 14891
Crack bridging ability under standard conditions	≥ 0,75 mm	A.8.2 EN 14891
Crack bridging ability at very low temperature (-20°C)	≥ 0,75 mm	A.8.3 EN 14891
Release of dangerous substances	See MSDS	Note ZA.1 EN 14891

Appropriate Technical Documentation and/or Specific Technical Documentation:

see technical data sheet
see MSDS

Website where the copy of the declaration of performance is made available:

www.vimark.com/en/

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

03.05.2021

VIMARK S.r.l. Peveragno (CN) Italy

Marco Massolino



Vimark S.r.l.
Strada Spartafino, 2 - 12016 Peveragno (CN) Italy
15
08.0015/2021

EN 14891:2012

FLEXO TWO

Water based waterproofing product, liquid applied, cement modified with polymer, with improved crack-bridging capacity at very low temperature (-20°C) and resistant to contact with chlorinated water (CMO2P), intended for external installation on walls and floors and pools below ceramic tiles (bonded with an C2 according to EN 12004)

Initial tensile adhesion strength	≥ 0,5 N/mm ²
Tensile adhesion strength after water contact	≥ 0,5 N/mm ²
Tensile adhesion strength after heat ageing	≥ 0,5 N/mm ²
Tensile adhesion strength after freeze-thaw cycles	≥ 0,5 N/mm ²
Tensile adhesion strength after contact with lime water	≥ 0,5 N/mm ²
Tensile adhesion strength after contact with chlorinated water	≥ 0,5 N/mm ²
Waterproofing	no penetration
Crack bridging ability under standard conditions	≥ 0,75 mm
Crack bridging ability at very low temperature (-20°C)	≥ 0,75 mm
Release of dangerous substances	See MSDS