



## DECLARATION OF PERFORMANCES

### 13.0002/2019

Annex III CPR - Regulation EU n. 305/2011 - Implementing Regulation EU n. 157/2014

<b>Unique identification code of the product-type:</b>	<b>POLYFIX</b>
<b>Intended use:</b>	General purpose rendering/plastering mortar (GP) for external and internal use
<b>Manufacturer:</b>	Vimark S.r.l. - Strada Spartafino, 2 - 12016 Peveragno (CN) - Italia
<b>Authorised representative:</b>	-
<b>System/s of AVCP:</b>	System no. 4
<b>Harmonised standard:</b>	EN 998-1:2016
<b>Notified bodies:</b>	-
<b>Declared performances:</b>	

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class A1	5.2.2 EN 998-1
Water absorption	W2	Table 2, L5 EN 998-1
Water vapour permeability	$\mu < 25$	Table 2, L8 EN 998-1
Adhesion	$> 0.5 \text{ N/mm}^2$ (FP) B	Table 2, L3 EN 998-1
Thermal conductivity	0.45 W/mK (tab. Mean value; P=50%)	Table 2, L10 EN 998-1
Durability	Evaluation based on provisions valid in the Intended place of use of the mortar	5.2.3.2 EN 998-1
Dangerous substances	See MSDS	Note ZA.1 998-1


**Appropriate Technical Documentation and/or Specific Technical Documentation:** see technical data sheet  
see MSDS

**Website where the copy of the declaration of performance is made available:** [www.vimark.com/en/](http://www.vimark.com/en/)

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

25.11.2019  
VIMARK S.r.l. Peveragno (CN) Italy

  
Marco Dutto



Vimark S.r.l.  
Strada Spartafino, 2 - 12016 Peveragno (CN) Italy  
**13**  
**13.0002/2019**

## EN 998-1:2016

### POLYFIX

General purpose rendering/plastering mortar (GP) for external and internal use

Reaction to fire	Class A1
Water absorption	W2
Water vapour permeability	$\mu < 25$
Adhesion	$> 0.5 \text{ N/mm}^2$ (FP) B
Thermal conductivity	0.45 W/mK (tab. Mean value; P=50%)
Durability	Evaluation based on provisions valid in the Intended place of use of the mortar
Dangerous substances	See MSDS