



DECLARATION OF PERFORMANCES

01.0003/2018

Annex III CPR - Regulation EU n. 305/2011 - Implementing Regulation EU n. 159/2014

Unique identification code of the product-type:	MALTA PARAMANO
Intended use:	Factory made designed general purpose masonry mortar (G) for use in elements subject to structural requirements
Manufacturer:	Vimark S.r.l. - Strada Spartafino, 2 - 12016 Peveragno (CN) - Italia
Authorised representative:	-
System/s of AVCP:	System no. 2+ System no. 4 for reaction to fire
Harmonised standard:	EN 998-2:2010
Notified bodies:	no. 1372 Tecno Piemonte S.p.A.

Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Compressive strength	Category M5	5.4.1 EN 998-2:2016
Bond strength	0.15 N/mm ²	5.4.2 EN 998-2:2016
Contents of chlorides	< 0.011 % Cl	5.2.2 EN 998-2:2016
Reaction to fire	Class A1	5.6 EN 998-2:2016
Water absorption	< 0.4 kg (m ² x min ^{0.5})	5.4.3 EN 998-2:2016
Water vapour permeability	μ 5/20	5.4.4 EN 998-2:2016
Thermal conductivity	0.61 W/mK (tab. Mean value; P=50%)	5.4.6 EN 998-2:2016
Durability	Evaluation based on provisions valid in the intended place of use of the mortar	5.4.7 EN 998-2:2016
Dangerous substances	See MSDS	Note ZA.1 998-2:2016

Appropriate Technical Documentation and/or Specific Technical Documentation: see technical data sheet
see MSDS


Website where the copy of the declaration of performance is made available: www.vimark.com/en/

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

02.05.2018

VIMARK S.r.l. Peveragno (CN) Italy



Marco Dutto



Vimark S.r.l.
Strada Spartafino, 2 - 12016 Peveragno (CN) Italy
08
01.0003/2018

EN 998-2:2016

MALTA PARAMANO

Factory made designed general purpose masonry mortar (G) for use in elements subject to structural requirements

Compressive strength	Category M5
Bond strength	0.15 N/mm ²
Contents of chlorides	< 0.011 % Cl
Reaction to fire	Class A1
Water absorption	< 0.4 kg (m ² x min ^{0.5})
Water vapour permeability	μ 5/20
Thermal conductivity	0.61 W/mK (tab. Mean value; P=50%)
Durability	Evaluation based on provisions valid in the intended place of use of the mortar
Dangerous substances	See MSDS